

SPECIFICATIONS

Scanners

Wired / Handheld



		1000 K/R/U	1090+	1100	1200
Performance	Category	CCD contact scanner	CCD contact scanner (for codes up to 90mm wide)	Linear imaging scanner	Laser scanner
	Optical sensor	2048 pixels	2048 pixels	3648 pixels	Laser
	Light source	Red LED (660 nm)	Red LED (650 nm)	Red LED (630 nm)	Visible laser diode (650 ±15 nm)
	Resolution	3 mil	4 mil	3 mil	4 mil
	Depth of field (depends on barcode resolution)	0 to 1 cm 0 to 0.4 in.	0 to 5 cm 0 to 2 in.	2.5 to 20 cm 1 to 7.9 in.	1 to 63 cm 0.4 to 25 in.
	Scanning angle	Pitch ± 70° Skew ± 40°	Pitch ± 70° Skew ± 70°	Pitch ± 70° Skew ± 70°	Pitch ± 70° Skew ± 32.5°
	PCS	Minimum 30%			
	Scan rate	100 scans/second			35 ± 5 scans/second
	Autosense mode	n/a		Yes	n/a
	Interfaces supported	RS232 / Keyboard wedge / Wand emulation (except 1000) / USB HID / USB Virtual Com / IBM 4683/4694			
	Barcodes supported	Codabar, Code 39, Code 93, Code 128, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, Pharmacodes, Plessey, RSS14, Telepen, UPC/EAN, and more			
	Programmable features	Data editing, interface selection, symbology configuration			
	Language support	US and UK English/French/Italian /Belgian/Norwegian/Swedish/Spanish/Portuguese/German			
Physical	Weight	265 g / 9.3 oz. (w/cable)	148 g / 5.2 oz.	165 g / 5.8 oz.	190 g / 6.7 oz.
	Color	Ivory		Light grey or dark grey	
	Switch	Rubber switch		Micro switch	
Electrical	Voltage	+5 V ±5%	+5 V ±5%	+5 V ±10%	+5 V ±5%
	Power Consumption Standby / Scanning / Maximum	15 mA / 60 to 80 mA / 85 to 110 mA	15 mA / 60 mA / 90 mA	15 mA / 80 mA / 160 mA	15 mA / 170 mA / 250 mA
User Environment	Operating temperature	0°C to 50°C / 32°F to 122°F			0°C to 40°C / 32°F to 104°F
	Storage temperature	-20°C to 60°C / -4°F to 140°F			-40°C to 60°C / -40°F to 140°F
	Operating/storage humidity	Non-condensing 10% to 90% / 5% to 95%			
	Impact resistance Multiple drops onto concrete	1.0 m (3.3 ft.) drops		2 m (6.6 ft.) drops	1.2 m (4 ft.) drops
	Electrostatic discharge	Conforms to ±15 kV air discharge and ±8 kV contact discharge			
EMC regulation	FCC / CE / C-tick / BSMI	FCC / CE / C-tick / BSMI / MIC	FCC / CE / C-tick / BSMI	FCC / CE / C-tick / BSMI / MIC	
Configuration	Setup options include Windows®-based ScanManager software (included), by direct connection or printing out barcode settings				
Accessories		Includes attached cable	Detachable cable, desk/wall mount included with 1100/1200. Optional autosense stand for 1100.		
Warranty		5 year			1 year

ACCESSORIES



©2008 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved.



Auto Sense Stand



1100/1105 & 1200 Holder

Can be used on tabletop or wall mounted



HEADQUARTERS
 CipherLab Co., Ltd.
 12F, 333 Dunhua S. Rd., Sec. 2
 Taipei, Taiwan 106
 Tel +886 2 8647 1166
 Fax +886 2 8732 2255
 www.cipherlab.com

CipherLab China
 Suite 1305, 1065A, Jaojiabang Rd.
 Xuhui District, Shanghai,
 China 200030
 Tel +86 21 3368 0288
 Fax +86 21 3368 0286

CipherLab USA
 2552 Summit Avenue
 Plano, Texas USA 75074
 Tel +1 469 241 9779
 Toll Free 888 300 9779
 Fax +1 469 241 0697

CipherLab EMEA
 Airedale House
 Clayton Wood Rise
 Leeds, LS16 6RF, UK
 Tel +44 113 274 7823
 Fax +44 113 274 7822

CipherLab Central Europe
 Willicher Damm 143-145
 41066 Mönchengladbach
 Germany