

SPECIFICATIONS

8400 series

Industrial Mobile Computer



		8400	8470	
Communication	Options	BT Class 2 compliance	BT Class 2 compliance IEEE 802.11 b/g	
	BT profile	SPP, DUN, HID		
	WLAN security	---	WEP, EAP, WPA (PSK), WPA2 (TKIP, AES, PSK)	
Performance	CPU	32-bit		
	Program memory	4MB flash		
	Data memory	4MB/16MB SRAM		
	MicroSD slot	Supports up to 8GB MicroSDHC		
	Main battery	Rechargeable lithium battery: 3.7V, 1800 mAh		
	Working hours ¹	110 hours ²	35 hours ³	
	Backup battery	Rechargeable lithium battery: 3.0V, 7.0 mAh		
	Data retention	25 days		
Physical characteristics	Barcode reader	Linear imager / Laser / 2D imager		
	Display	160 × 160 display, white LED backlight		
	Keypad	29 or 39 rubber keys, white LED backlight		
	Alert	Two dual-color LEDs (red/green, blue/green), vibrator, volume programmable beeper		
	Dimension L x W x H	170.6 × 72.1 × 40.6 mm / 6.7 × 2.8 × 1.6 in.		
	Weight	295 g / 10.4 oz. laser model including battery		
User environment	Operating temperature	-10° to 60°C / 14° to 140°F		
	Storage temperature	-20° to 70°C / -4° to 158°F		
	Humidity non-condensed	Storage 5% to 95% Operating 10% to 90%		
	Impact resistance	Multiple 1.5 m drops onto concrete, 5 drops on each side		
	Tumbling test	1000 tumbles at 100cm		
	Splash/dust resistance	IP54		
	Electrostatic discharge	±15kV air discharge ±8kV direct discharge		
	EMC regulation	BSMI, CE, C-Tick, NCC, FCC, SRMC		
Programming	CipherLab Power Suite FORGE Application Generator including data transmission OCX, STREAM Wireless Studio, MIRROR Terminal Emulation, BLAZE C Compiler and BASIC Compiler			
Accessories	Charging and communication cradle, Ethernet cradle, GSM/GPRS cradle (EDGE/Quad-band), modem cradle, 4-slot battery charger, USB charging and communication cable, RS232 charging and communication cable, protective cover			
Warranty	1 year			

¹ Based on one standard laser scan per five seconds with backlight off.
² Batch mode/BT off: 110 hours / BT on is 65 hours.
³ BT off/IEEE 802.11 b/g on. The test is based on one broadcasting packet per second.

ACCESSORIES



Charging and Communication Cradle



Protective Cover



4-Slot Battery Charger



56kps Modem Cradle

©2009 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners.



HEADQUARTERS
 CipherLab Co., Ltd.
 12F, 333 Dunhua S. Rd., Sec. 2
 Taipei, Taiwan 10669
 Tel +886 2 8647 1166
 Fax +886 2 8732 3300
 www.cipherlab.com

CipherLab China
 Suite 1305, 1065A, Jaojiabang Rd.
 Xuhui District, Shanghai,
 China 200030
 Tel +86 21 3368 0288
 Fax +86 21 3368 0286

CipherLab USA
 2552 Summit Avenue
 Plano, Texas USA 75074
 Tel +1 469 241 9779
 Toll Free 888 300 9779
 Fax +1 469 241 0697

CipherLab Central Europe
 Willicher Damm 143-145
 41066 Mönchengladbach
 Germany
 Tel +49 2161 56230 0
 Fax +49 2161 56230 22