

# SPECIFICATIONS

## 9400 series

### Industrial Mobile Computer

CipherLab 9400 and 9500 are both rugged, Windows-based mobile computers, ready to go to work for you.



	Model	9400	9470	9480	9490
<b>Performance</b>	Operating system	Microsoft® Windows® CE 5.0 Professional			
	CPU	Intel® XScale™ PXA270 @ 520 MHz			
	Memory	128MB Flash ROM / 128MB SDRAM			
	Expansion	Mini SD® slot			
	Operating power	Removable, rechargeable 3.7 V 1800 mAh Li-ion battery			
		Adapter: AC 110 V / 220 V input, DC 6 V / 3.3 A output via cradle			
	Working hours <sup>1</sup>	10 hours batch mode		8 hours WLAN mode	
	Backup power	3.7 V 70 mAh Lithium battery			
		Data sustained 20 hours minimum			
	Alerts	Audio speaker / Vibrator / Tri-color LEDs			
Microphone	via Bluetooth or wired headset				
<b>Wireless Communication</b>	WLAN	-	Wi-Fi 802.11 b/g 250 m line of sight <sup>2</sup>	-	Wi-Fi 802.11 b/g 250 m line of sight <sup>2</sup>
	WPAN	Bluetooth Class 2			
	WWAN	-	-	GSM/GPRS/EDGE (Quad-band)	
<b>Data Capture</b>	Barcode scanning	Linear imager / Laser / 2D imager			
	RFID reader/writer	Frequency: 13.56 MHz Supported tags: ISO 14443A, ISO 14443B, ISO 15693, Tag-it			
	Digital camera	2 megapixels CMOS			
<b>Physical Characteristics</b>	Display	3.5" Color VGA or QVGA, TFT transfective, touch screen, LED backlight			
	Keypad	28 shared or 59 full alphanumeric LED backlight keys			
	LED	Green, red, blue tri-color			
	Size (L x W x H) Weight	170 x 90 x 38 mm / 6.7 x 3.5 x 1.5 in 400 g / 14.1 oz., (configuration dependent)			
<b>User Environment</b>	Operating temp.	-10°C to 50°C / 14°F to 122°F			
	Storage temp.	-20°C to 60°C / -4°F to 140°F			
	Humidity	5% to 95% non-condensing			
	Impact resistance	Multiple 1.5 m (5 ft.) drops onto concrete (5 drops on each facet) 2000 tumbles (50cm) / IP64			
	Electrostatic discharge	± 15 kV air discharge; ± 8 kV direct discharge			
EMC regulation	CE, FCC, RSS-210, TELEC, C-Tick				
Programming	eMbedded Visual C++ 4.0, Visual Studio.NET, Visual Studio 2005, Windows CE SDK, Reader Configuration Utility, CipherLab Power Suite FORGE Application Generator, STREAM Wireless Studio, MIRROR Terminal Emulation, Wavelink, MCL				
Accessories	Charging and USB client/host communications cradle, vehicle cradle, travel cradle, 4-slot terminal charger, 4-slot battery charger, belt holster, protective cover, pistol grip, USB Ethernet adapter				
Warranty	1 year				

<sup>1</sup> Based on one standard laser scan per five seconds with backlight on

<sup>2</sup> Effective coverage depends on user environment and equipment deployment. It is highly recommended to conduct a site survey before actual deployment.

### ACCESSORIES

#### Charging and Communication Cradle USB client / USB host



#### Vehicle Cradle



#### Travel Cradle



#### Pistol Grip



#### USB Ethernet Adapter



#### Belt Holster



#### Protective Cover



#### 4-Slot Battery Charger



#### 4-Slot Charging Cradle



DIN EN ISO 9001

©2008 CipherLab Co., Inc. All specifications are subject to change without notice. All rights reserved. Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries and is used by CipherLab under license from owner. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. Other trademarks and trade names are those of their respective owners.



**HEADQUARTERS**  
CipherLab Co., Ltd.  
12F, 333 Dunhua S. Rd., Sec. 2  
Taipei, Taiwan 106  
Tel +886 2 8647 1166  
Fax +886 2 8732 2255  
www.cipherlab.com

**CipherLab China**  
Suite 1305, 1065A, Jaojiabang Rd.  
Xuhui District, Shanghai  
China 200030  
Tel +86 21 3368 0288  
Fax +86 21 3368 0286

**CipherLab USA**  
2552 Summit Avenue  
Plano, Texas, USA 75074  
Tel +1 469 241 9779  
Toll Free 888 300 9779  
Fax +1 469 241 0697

**CipherLab EMEA**  
Airedale House  
Clayton Wood Rise  
Leeds, LS16 6RF, UK  
Tel +44 113 274 7823  
Fax +44 113 274 7822